UL Product iQ™

ZPMV2.E352816 - Wiring, Printed - Component

Wiring, Printed - Component

See General Information for Wiring, Printed - Component

KINGFORD PCB ELECTRONICS CO LTD E352816
Flat Rm 704 7F
Bright Way Tower
33 Mong Kok Road Mong Kok
Kowloon, HONG KONG

Type	Cond Width Min mm(in)	Min Edge mm(in)	Cond Thk mic(mil)	SS/ DS/ DSO	Max Area Diam mm(in)	Solder Limits °C	sec	Assembly Solder Process (IPC) °C	Cycles	Oper Temp °C	Flame Class	Meets UL796 DSR	C T I
Multilayer printed wiring boards.													
KF-4M	0.08 (0.003)	0.1 (0.004)	17 (0.67) Int:102	DS	76.2 (3.0)	288	20	-	-	130	V-0	All	*
M3	0.08 (0.003)	0.1 (0.004)	17 (0.67) Int:102	DS	76.2 (3.0)	288	20	-	-	130	V-0	All	*
M4	0.15 (0.006)	0.45 (0.018)	17 (0.67) Int:35	DS	25.4 (1.0)	280	10	-	-	110	V-0	All	*
Single layer metal base printed wiring boards.													
A1	0.10 (0.004)	0.128 (0.005)	17 (0.67)	SS	25.4 (1.0)	290	20	-	-	130	V-0	All	0
Single Layer Metal Base Printed Wiring Boards.													
A2	0.1 (0.004)	0.15 (0.006)	17 (0.67)	SS	50.8 (2.0)	288	20	-	-	130	V-0	All	*
A3	0.1 (0.004)	0.15 (0.006)	17 (0.67)	SS	50.8 (2.0)	288	20	-	-	115	V-0	All	*
Single layer printed wiring boards.													
S1	0.02 (0.0008)	0.06 (0.002)	17 (0.67)	DS	25.4 (1.0)	280	10	-	-	110	V-0	All	*
Singlelayer printed wiring boards.													
KF-D-4V0	0.08 (0.003)	0.1 (0.004)	17 (0.67)	DS	76.2 (3.0)	288	20	-	-	130	V-0	All	*

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name, or file number and type designation and the Recognized Component Mark,  . May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2021-01-20
